



## IP65 Level EV Fast Charger Station Type 2 AC 7kw Charger EV Charging Pile With Touch Button

Our Product Introduction

for more products please visit us on [evstationcharger.com](http://evstationcharger.com)

### Basic Information

- Place of Origin: China
- Brand Name: MINKO
- Certification: CE(ICR lab), UKCA, ROHS, ISO, REACH
- Model Number: C32EU-32A
- Minimum Order Quantity: 5 pieces
- Price: negotiation
- Packaging Details: L210xW85xH52 (mm)
- Delivery Time: 8 -10 working days
- Payment Terms: T/T, Western Union, MoneyGram, Paypal, Skrill, Transferwise
- Supply Ability: 1000000 pieces per month



### Product Specification

- Charging Plug: IEC 62196 Type2
- Rated Voltage: AC 230V / Single Phase
- Rated Current: 32A
- Rated Power: 7.36kW
- Input Power: 250V Max
- Operating Temperature: -35°C To 50°C
- Start Method: Plug And Play
- Electric Cable: IP65 Circuit Breaker
- Highlight: 250v level 2 charger portable, 7kw ev portable charger type 2, ip65 ev portable charger type 2



### More Images



## Product Description

### IP65 Level EV Fast Charger Station Type 2 AC 7kw Charger EV Charging Pile With Touch Button

#### Detailed specification:

Portable EV Charger, with power ratings of 3KW, 7 kW, is suitable for different types of vehicles.

Adjustable current, suitable for various scenarios.

The Voltage and Current are stable during charging, which can protect the battery and delay using time.

We can use normally in ultra-high temperature environment up to 50°C.

It can also be used normally in the -35°C.

#### EN Standard Strong Patience.

The charging cable meets the latest EN standard request of an electric vehicle charging cable. Highly resistant to the cold & heat,

with the cable maintaining flexibility at -40°C, therefore withstanding colder conditions.

#### TPU Cable.

Highly resistant to bending, protecting the internal wiring harness to function normally under repeated bending conditions.

#### Climate Friendly Stronger & Anti-aging.

The halogen-free charging cable is climate friendly, meeting the EU's and USA's environmental standards. The tight, strong molecular structure provides a long-lasting charging cable solution, ensuring greater service life.

#### Arcing Design.

Unique self-cleaning design ensures that impurities on the surface of the pins can be removed during each plug-in process.

#### Ergonomic Design and Integrated Design

Angled horizontal bending design, in line with the habit of manual force which allows for convenient plugging & unplugging.

K10 rated with an integrated design ensuring that you can charge safely in all weather conditions.

#### Better Conductivity.

Silver plating on the pins ensures greater conductivity, charging efficiency and reduces heat generation.

#### Temperature Monitoring

Detects if the temperature is higher than the 'set safe' value, if this occurs, the current will automatically be cut off.

|                         |   |           |                           |           |           |
|-------------------------|---|-----------|---------------------------|-----------|-----------|
| Charging plug           | Type 2  |           | Type 1                    |           |           |
| Model No.               | C16EU-16A   | C32EU-32A | W16US-16A                 | W32US-32A | W40US-40A |
| Rated voltage           | AC 230V / Single phase  |           | AC 110-240V/ Single phase |           |           |
| Rated current           | 16A   | 32A       | 16A                       | 32A       | 40A       |
| Rated power             | 3.68kW  | 7.36kW    | 3.84kW                    | 7.68kW    | 9.6kW     |
| Certificates            | CE, UKCA, ROHS,ISO, REACH, FCC  |           |                           |           |           |
| Protection rank         | IP65  |           |                           |           |           |
| Earth leakage protector | 30m AC  |           |                           |           |           |
| input power             | 250V Max  |           |                           |           |           |
| length                  | European standard, Default 5M   |           | US standard,Default 7.4M  |           |           |
| start method            | Plug and Play   |           |                           |           |           |
| Operating temperature   | -35°C to 50°C   |           |                           |           |           |
| electrical protection   | Over current protection, residual current protection, grounding protection, surge protection, Over voltage /under voltage protection, over voltage/ under frequency protection, over temperature protection |           |                           |           |           |
| Applied Materials       | Housing: Black thermoplastic PC940. Corrosion and wear protection. Cable: 4.5M black with TPU jacket. With CE and TUV mark issued by TUV.   |           |                           |           |           |
| Warranty                | 1 Years for the whole machine   |           |                           |           |           |

#### Feature:

1. The product complies with the Low Voltage Directive 2014/35/EU, IEC61851-1:2019
2. IP65, weatherproof; leakage protection; impact resistance
3. Charging status and working error are simply displayed by LED indicator light and LCD screen
4. Optional unction of current selection button,
5. 8A-32A free switching current





**Caution:**

Don't submerge the EV charging cable in water.

Don't step on, fold or knot the cable.

Don't drop the EV charging box or place a heavy object on it.

Don't place the charging cable near high temperature object when charging.

Don't operate the EVSE in temperatures beyond its operating range of -25°C to 55°C.

Power-supply side input cable should be at least 3\*2.5mm (recommended 3\*4mm), with a standard 16A socket. It is suggested that

the power distribution is done by the professionals.

Don't put fingers into the charging connector when the power plug is still connecting to the power.

Don't use this EV charging box when the cable is damaged.

The EV charging box is only for EV charging using.

Don't use this device with other brand's extension cord or adapter.



**MINKO (SZ) TECHNOLOGY CO., LIMITED**



+8613539872669



yumiko@szminko.com



evstationcharger.com

309 West Lake Industrial Zone, Cuishan Road, Dongxiao Street, Luohu District, SZ